HEIZUNGSPUMPE INOVA NH II

# Heizungspumpe INOVA NH II 25/80, We.

Article number 6632580238
Product page https://www.speck-pumps.com/en/p/heizungspumpe-inova-nh-ii-25-80-we-6632580238




## Description

Our heating pump is a true all-rounder. Equipped with an LED display, this product can be used in a variety of ways. The setting options for constant, variable, or fixed speed make this series a pump for all applications.

## Areas of use

Hot water heating systems of all types Especially for single- and two-family homes Industrial circulation systems Air conditioning systems Closed cooling circuits

## Version

Glandless circulation pump with a stall-current-proof synchronous motor and integrated electronic control for continuously variable performance adjustment, optionally with Δp-c (constant differential pressure), Δp-v (variable differential pressure), or 3-speed fixed speed. Standard high-efficiency pump Control module with LED display for easy setting of the setpoint and control mode Display of current power consumption ErP-compliant, EEI ≤ 0.20 Minimum power consumption only 4 watts Self-venting Fast electrical connection via connector plug Includes thermal insulation shell Flow medium: Heating water according to VDI 2035. Water/glycol mixtures in a max. ratio of 1:1.

## Material short text

Heizungspumpe INOVA NH II 25/80, We.

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 4.2 m³/h |
| Förderhöhe | 7.5 mWS |
| Operating pressure max. | 6 bar |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 min-1 |
| Motor phases | 1~ |

| | |
|---|---|
| Degree of protection | IP X2 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input max. | 0.07 kW |
| Voltage (max.) | 1~ 230 V |
| Frequency | 50 Hz |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | EEI |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur | 95 ° C |
| Temperature min. | -10 – 95 ° C |

## Dimensions & logistics

| | |
|---|---|
| Product length | 133 mm |
| Product width | 93 mm |
| Product height | 130 mm |
| Customs tariff number | 84137030 |