SUPS 28

SUPS 28-4 (3 ~400V)

Article number 5161280047

Product page https://www.speck-pumps.com/en/p/sups-28-4-3-400v-5161280047



Description

Die Unterwasserpumpen zeichnen sich durch eine hohe Wirtschaftlichkeit, lange Lebensdauer und einen gekapselten Unterwassermotor aus. Alle medium berührten Teile sind aus Edelstahl.

Areas of use

Water supply. Irrigation. Fountain systems. Heat pumps. Rainwater harvesting

Material short text

SUPS 28-4. Dr.. 4.0 kW

Technical data

Hydraulic power

Flow rate	38 m³/h
Förderhöhe	45 mWS
Operating pressure max.	25 bar

Motor & drive

Drehzahl	2,800 min-1
Motor phases	3 ~
Degree of protection	IP 68
Insulation class	B

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	4 kW
Voltage (max.)	3~ 400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Operating conditions & water

Umgebungstemperatur	30 ° C
Temperature min.	30 ° C

Dimensions & logistics

Product length	1,199 mm
Product width	0 mm
Product height	0 mm
Net weight	34 kg
Customs tariff number	84137029