BADU PRIME 25-48

BADU Prime 30

Article number	2190308038
GTIN/EAN	4260673451561
Product page	https://www.speck-pumps.com/en/p/badu-prime-30-2190308038



Description

Highly efficient motor suitable for frequency converter operation For large pools, swimming pools and absorber systems

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 6 l Suction screen mesh size approx. 3.0 x 2.8 mm

Material short text

BADU Prime 30, 1~, 1,50kW, blau

Technical data

Hydraulic power

Flow rate	30 m³/h
Förderhöhe	19 mWS
Operating pressure max.	0 bar

Motor & drive

Drehzahl	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	2 kW
Power output P_2 (max.)	1.5 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

General / Product features

Certification	TÜV, Garantie 5 Jahre

Filtration

Lint catcher capacity	6 l

Connections & piping

Connection, inlet / suction side	75 mm
Connection, discharge side	75 mm
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	777 mm
Net weight	24.2 kg
Customs tariff number	84137051