BADU 93

# BADU 93/45 H

Article number 2193450037

Product page https://www.speck-pumps.com/en/p/badu-93-45-h-2193450037



## Areas of use

Swimming pool water circulation in filter systems, each installed max. 3 m above or below the water level.

## Material short text

BADU 93/45 H, 3~, 2,60 kW, GBZ-Ausf.

## Technical data

### Hydraulic power

| | |
|---|---|
| Förderhöhe | 90.407 mWS |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,840 min-1 |
| Motor phases | 3~ |
| Motor frame size | 100 |
| Degree of protection | IP 55 |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 3 kW |
| Power output $P_2$ (max.) | 2.6 kW |
| Power input max. | 3 kW |
| Voltage (max.) | 3~ Y/Δ 400/230 V |

### Filtration

| | |
|---|---|
| Lint catcher capacity | 8 l |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | 110 d |
| Connection, discharge side | 110 d |

| | |
|---|---|
| Recommended suction line diameter | 110 mm |
| Recommended discharge line diameter | 90 mm |

### Operating conditions & water

| | |
|---|---|
| Total salt concentration | 0.5 % |

## Dimensions & logistics

| | |
|---|---|
| Product length | 872 mm |
| Product width | 250 mm |
| Product height | 452 mm |
| Customs tariff number | 84137051 |