TOP 90

# TOP 90 VOX D

Article number 6422075127

Product page https://www.speck-pumps.com/en/p/top-90-vox-d-6422075127



## Description

Optimal drainage through submersible pumps made of corrosion-resistant materials from Speck, offering a highly flexible application and use for more than just water.

## Areas of use

Basement drainage Drainage of pump shafts Wastewater disposal Rainwater pumping Groundwater pumping

## Version

Fully submersible submersible pump made of stainless steel. Motor with built-in thermal overload protection (for AC). Ready to connect with a 10 m cable and Schuko plug (for AC), with a free cable end (for three-phase). AC = AC 1~ 230 V, with floating switch D = Three-phase 3~ 400 V, without floating switch VOX = Open impeller Pump medium: Pure water, wastewater, and dirty water, without long-fiber components.

## Material short text

TOP 90 VOX D, 0,55 kW

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 24 m³/h |
| Förderhöhe | 7.5 mWS |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 min-1 |
| Motor phases | 3~ |
| Degree of protection | IP 68 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0.8 kW |
| Power output $P_2$ (max.) | 0.55 kW |
| Voltage (max.) | 3~ 400 V |
| Frequency | 50 Hz |
| Cable length | 10 m |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | IE3 |

### Connections & piping

| | |
|---|---|
| Connection, discharge side | 2 Rp |

## Dimensions & logistics

| | |
|---|---|
| Product length | 0 mm |
| Product width | 0 mm |
| Product height | 486 mm |
| Net weight | 16.2 kg |
| Gross weight | 0 kg |
| Customs tariff number | 84137021 |