SPR-VLT

# SPR-VLT-407

Article number 5606140710

Product page https://www.speck-pumps.com/en/p/spr-vlt-407-5606140710



## Description

The frequency control for single-pump pressure booster systems can be mounted directly on the wall and ensures optimal adjustment of the pump to the application.

## Areas of use

Water supply Cooling circuit Irrigation Industrial applications

## Version

The SPR-VLT speed controller optimally adapts the pump to the system. The pump controller is available for the following control types: Setpoint control External setpoint Fixed setpoint The SPR-VLT speed controller can be mounted directly on the wall. The speed controller is equipped with a plain-text display, PTC thermistor connection, operating mode selector buttons, and a repair switch. The system is factory-configured.

## Material short text

SPR-VLT-407, 3 kW

## Technical data

### Motor & drive

| | |
|---|---|
| Motor phases | 3~ |
| Degree of protection | IP 66 |

### Electrics

| | |
|---|---|
| Power output $P_2$ (max.) | 3 kW |
| Voltage (max.) | 3~ 400 V |
| Frequency | 60 Hz |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur | 0 ° C |

| | |
|---|---|
| Temperature min. | 0 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 8.9 kg |
| Customs tariff number | 85371098 |