BADU JET SMART

BADU JET Smart FMS 3~ 2,2 kW

Article number 2300200000

Product page https://www.speck-pumps.com/en/p/badu-jet-smart-fms-3-2-2-kw-2300200000



Description

Powerful in-ground system. Includes everything a perfect pool needs.

Areas of use

For wall installation in all pool designs, as an attraction, for fitness, as a wave or bubble bath, or for underwater massage following medical advice. Swimming without turning is also possible in small pools.

Version

A powerful BADU pump connected via a suction and pressure line draws water through a flush-mounted plastic housing and nozzle housing in the pool. A powerful jet of water is returned to the pool via an adjustable nozzle that can be swiveled 60° in all directions. Numerous openings around the nozzle housing ensure extremely low suction flow. The pneumatic on/off switch and the controls for the tingling air bubble bath are located in the nozzle housing.

Material short text

BJ Smart FMS, 3~

Technical data

Hydraulic power

Flow rate	45 m³/h

Motor & drive

Insulation class	F

Electrics

Power input P_1 (max.)	2.74 kW
Power output P_2 (max.)	2.2 kW
Frequency	50 Hz

General / Product features

Product range	BADU Allround

Connections & piping

Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Nozzles & counter-current system

Number of nozzles	1 St
Nozzle diameter	40 mm
Nozzle swivels in all directions	60 °
Outlet pressure at the nozzle	1 bar
Outlet velocity, centred 2 m in front of the nozzle	1 m/s
Massage pressure max.	1.7 bar

Operating conditions & water

Umgebungstemperatur	40 ° C

Dimensions & logistics

Customs tariff number	84798997