SGM-DA 201

SGM-DA 201

Article number 5698510000

Product page https://www.speck-pumps.com/en/p/sgm-da-201-5698510000



Description

These fully automatic small pressure booster systems are ideal universal pumping stations. Equipped with a 20-liter diaphragm pressure tank, a pressure gauge, and a pressure switch for automatic on/off.

Areas of use

Rainwater harvesting Car washes Equipment construction Shipping

Version

SG/SGM: Self-priming centrifugal pump, suitable for pure, water-like liquids. Equipped with lifetime-lubricated motor bearings. Shaft sealed by a mechanical seal. AC version with on/off switch in the terminal box, 1.5 m cable, and Schuko plug. SGM-Speckmat: Includes Speckmat 1 control unit for automatic, pressure-dependent start-up, flow-dependent shutdown, and integrated dry-run protection. SG/SGM-DA: Includes a 20 l stainless steel diaphragm pressure vessel, pressure gauge, and pressure switch for automatic start-up and shutdown. Special versions Special voltages Special mechanical seals Fluid: Pure cold water, as well as fluids that do not chemically or mechanically attack the pump materials.

Material short text

Klein-DEA SGM-DA 201, We., 0,88 kW

Technical data

Hydraulic power

Flow rate	4 m³/h
Förderhöhe	50 mWS
Operating pressure max.	6 bar

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~

Degree of protection	IP 54
Insulation class	F

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	0.9 kW
Voltage (max.)	1~ 230 V
Input voltage	230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE2

Connections & piping

Connection, inlet / suction side	Rp 1¼
Connection, discharge side	Rp 1

Operating conditions & water

Umgebungstemperatur	40 ° C
Temperature min.	45 ° C

Dimensions & logistics

Product length	490 mm
Product height	575 mm
Net weight	19.5 kg
Gross weight	20.5 kg
Customs tariff number	84798997