BADU BLOCK 50

BADU Block 50-200

Product page https://www.speck-pumps.com/en/p/badu-block-50-200-p51017



Description

Characteristic curves, as well as dimensional drawings and the various material combinations can be found in detail in our design program at speck-select.com

Areas of use

Swimming pool water circulation for filtration and filter flushing, as well as the operation of swimming pool attractions in public swimming pools. > Outdoor and indoor pools > Thermal, medicinal, and spa baths > Pools with elevated brine concentrations > Water treatment, e.g., filter system construction > Leisure facilities > Attractions, e.g., water slides > Shipbuilding4) > Industry, e.g., cooling water systems > Water supply, e.g., irrigation

Version

Non-self-priming, single-stage volute casing pump in a vertical close-coupled design. The back-pressure design allows for easy replacement of the drive unit without disassembling the piping. The low speed ensures quiet operation and low wear. The pump is equipped with replaceable, corrosion-resistant wear rings. The closed, balanced impeller can be individually adapted to the specific operating conditions. Balancing is carried out to grade class 6.3 according to DIN ISO 1940. This ensures optimal smooth operation and a long service life of the entire pump. Filter housing capacity BADU Block 32/ up to 65/ approx. 13 l BADU Block 80/ up to 125/ approx. 29 l BADU Block 150/ approx. 71 l Suction strainer mesh size approx. Ø 3 mm

Technical data

Hydraulic power

Flow rate	60 m³/h
Förderhöhe	10 – 17 mWS
Operating pressure max.	2.5 bar

Motor & drive

Drehzahl	1.45 – 1.75 min-1
Motor frame size	112 M
Degree of protection	IP 55

Insulation class	F

Electrics

Power output P_2 (max.)	5.5 kW
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Filtration

Lint catcher capacity	13 l

Connections & piping

Connection, inlet / suction side	DN 100
Connection, discharge side	DN 50

Dimensions & logistics

Customs tariff number	84137051