BADU 21-40

BADU 21-40/63 G

Article number 2340630137
Product page https://www.speck-pumps.com/en/p/badu-21-40-63-g-2340630137



Description

Universal, small circulation pump. Reliable and space-saving. For tubs and pools, counter-current systems, and pool cleaning devices.

Areas of use

Freshwater

Version

Close-coupled pump with bellows mechanical seal, mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. The discharge port can be rotated 90° in increments. Can also be used vertically with the pump at the bottom. Self-draining when installed vertically.

Material short text

BADU 21-40/63 G, 3~, 0,55 KW, G 2

Technical data

Hydraulic power

Flow rate	17 m³/h
Förderhöhe	0 – 12.4 mWS
Operating pressure max.	2.5 bar

Motor & drive

Drehzahl	2,850 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.75 kW
Power output P_2 (max.)	0.55 kW
Voltage (max.)	3~ 400/230 V
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2 G
Connection, discharge side	2 G
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Operating conditions & water

Total salt concentration	5 g/l

Dimensions & logistics

Product length	317 mm
Product width	0 mm
Product height	0 mm
Customs tariff number	84137051