BADU 21-40

BADU 21-40/63 G

Article number 2340630138
Product page https://www.speck-pumps.com/en/p/badu-21-40-63-g-2340630138



Description

Universal, small circulation pump. Reliable and space-saving. For tubs and pools, counter-current systems, and pool cleaning equipment.

Areas of use

As a jet pump for bathtubs and whirlpools, massage devices, air conditioning systems and pool cleaning devices up to 30 m³/h flow rate.

Version

Close-coupled pump with bellows mechanical seal, mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. The discharge port can be rotated 90° in increments. Can also be used vertically with the pump at the bottom. Self-draining when installed vertically.

Material short text

BADU 21-40/63 G, 1~, 0,55 kW, G 2, -EV-

Technical data

Hydraulic power

Flow rate	16 m³/h
Förderhöhe	12.4 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.85 kW
Power output P_2 (max.)	0.55 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

Filtration

Lint catcher capacity	0 l

Connections & piping

Connection, inlet / suction side	2 G
Connection, discharge side	2 G
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	343 mm
Net weight	8.1 kg
Customs tariff number	84137051