BADU 21-40

# BADU 21-40/64 G

Article number 2340640138
Product page https://www.speck-pumps.com/en/p/badu-21-40-64-g-2340640138



## Description

Universal, small circulation pump. Reliable and space-saving. For tubs and pools, counter-current systems, and pool cleaning equipment.

## Areas of use

As a jet pump for bathtubs and whirlpools, massage devices, air conditioning systems and pool cleaning devices up to 30 m³/h flow rate.

## Version

Close-coupled pump with bellows mechanical seal, mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. The discharge port can be rotated 90° in increments. Can also be used vertically with the pump at the bottom. Self-draining when installed vertically.

## Material short text

BADU 21-40/64 G, 1~, 0,75 kW, G 2, -EV-

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 18 m³/h |
| Förderhöhe | 13 mWS |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 min-1 |
| Motor phases | 1~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 1.05 kW |
| Power output $P_2$ (max.) | 0.75 kW |
| Voltage (max.) | 1~ 230 V |
| Frequency | 50 Hz |

### Filtration

| | |
|---|---|
| Lint catcher capacity | 0 l |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | 2 G |
| Connection, discharge side | 2 G |
| Recommended suction line diameter | 63 mm |
| Recommended discharge line diameter | 63 mm |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur | 40 ° C |
| Total salt concentration | 5 g/l |

## Dimensions & logistics

| | |
|---|---|
| Product length | 317 mm |
| Net weight | 9.3 kg |
| Customs tariff number | 84137051 |