
BADU 21-41

BADU 21-41/64 G

Article number 2341640138

Product page https://www.speck-pumps.com/en/p/badu-21-41-64-g-2341640138



Description

Connection variant of the universal circulation pump BADU 21-40/6. For tubs and pools, countercurrent systems, and pool cleaning devices.

Areas of use

As a jet pump for bathtubs and counter-current systems, whirlpools, massage devices, air conditioning systems and cleaning devices up to 30 m³/h flow rate.

Version

Close-coupled pump with bellows mechanical seal, mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. The discharge port can be rotated 90° in increments. Can also be used vertically with the pump at the bottom. Self-draining when installed vertically.

Material short text

BADU 21-41/64 G, 1~, 0,75 kW

Technical data

Hydraulic power

Flow rate	18 m³/h
Förderhöhe	13 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	1.05 kW
Power output P_2 (max.)	0.75 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

Filtration

Lint catcher capacity	0 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	2 G
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	331 mm
Net weight	9.4 kg
Customs tariff number	84137051