BADU 21-81

BADU 21-81/32R

Article number	2381320238
GTIN/EAN	4260673452858
Product page	https://www.speck-pumps.com/en/p/badu-21-81-32r-2381320238



Description

Connection variant of the universal circulation pump BADU 21-80. For whirlpools, counter-current systems, and swimming pool attractions.

Areas of use

Swimming pool and industrial filter systems, countercurrent systems, air conditioning systems, swimming pool attractions, cleaning equipment, and much more – up to 90 m³/h flow rate.

Material short text

BADU 21-81/32R G, 1~, 2,20 kW

Technical data

Hydraulic power

Flow rate	55 m³/h
Förderhöhe	11.8 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	2.9 kW
Power output P_2 (max.)	2.2 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

Filtration

Lint catcher capacity	0 l

Connections & piping

Connection, inlet / suction side	90 mm
Connection, discharge side	90 mm
Recommended suction line diameter	110 mm
Recommended discharge line diameter	110 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	513 mm
Net weight	19 kg
Customs tariff number	84137051