BADU Delta Eco VS

Article number	2103281138
GTIN/EAN	4260673450908
Product page	https://www.speck-pumps.com/en/p/badu-delta-eco-vs-2103281138



Description

Neuer High-Class-Standard mit Drehzahlregelung. Hochwertige Filterumwälzpumpen für Profis.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Suction strainer mesh size approx. 2.2 x 2.2 mm

Material short text

BADU Delta Eco VS, 1~, 1,10 kW

Technical data

Hydraulic power

Flow rate	16 m³/h
Förderhöhe	20.7 mWS

Motor & drive

Drehzahl	600 – 3,000 min-1
Motor phases	1-phasig
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.03 – 1.4 kW

Power output P_2 (max.)	0.01 – 1.1 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

General / Product features

Product range	BADU Premium, BADU Green
Certification	TÜV, Patent, Green

Filtration

Lint catcher capacity	4 l
Strainer basket mesh size	ca. 2,2 x 2,2 mm

Connections & piping

Connection, inlet / suction side	63
Connection, discharge side	63
Recommended suction line diameter	63 mm
Recommended discharge line diameter	63 mm

Acoustics

Schalldruckpegel	35.7 – 665 dB[A]

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 %

Dimensions & logistics

Product length	654 mm
Net weight	14 kg
Customs tariff number	84137051