BADU EASYFIT

BADU EasyFit 45

Article number	2076400038
GTIN/EAN	4260673451707
Product page	https://www.speck-pumps.com/en/p/badu-easyfit-45-2076400038



Description

Flexibility champion with 6 different connection sets. For use in virtually any filter system, regardless of manufacturer.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU EasyFit 45, 1~, 2,20 kW, ohne Kabel

Technical data

Hydraulic power

Flow rate	45 – 51 m³/h
Förderhöhe	19.7 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	2.92 kW

Power output P_2 (max.)	2.2 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz

Energy efficiency

Energy efficiency class	D

General / Product features

Certification	TÜV, Patent

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	75 mm
Connection, discharge side	75 mm
Recommended suction line diameter	75 mm
Recommended discharge line diameter	75 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	601 mm
Net weight	24.7 kg
Customs tariff number	84137051