BADU ECO TOUCH-PRO II

BADU Eco Touch-Pro II

Article number	2190008038
GTIN/EAN	4260673454258
Product page	https://www.speck-pumps.com/en/p/badu-eco-touch-pro-ii-2190008038



Description

Rock-solid and fully optimized for efficiency. Intelligent circulation pump for beginners.

Areas of use

Swimming pool water circulation in filter systems, which can be installed a maximum of 3 m above or below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 3 l Suction screen mesh size approx. 3.2 x 2.6 mm

Material short text

BADU Eco Touch-Pro II, 1~, 0,75kW

Technical data

Hydraulic power

Flow rate	25 m³/h
Förderhöhe	15 mWS

Motor & drive

Drehzahl	1,000 – 2,830 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	B

Electrics

Power input P_1 (max.)	1.05 kW

Power output P_2 (max.)	0.75 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	3 l

Connections & piping

Connection, inlet / suction side	63 mm
Connection, discharge side	50 mm
Recommended suction line diameter	63 mm
Recommended discharge line diameter	50 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	602 mm
Product width	196 mm
Product height	293 mm
Net weight	9 kg
Customs tariff number	84137051