BADU MAGIC II

BADU Magic II / 11

Article number	2191118038
GTIN/EAN	4260673450670
Product page	https://www.speck-pumps.com/en/p/badu-magic-ii-11-2191118038



Description

Ideal entry-level pump with a wide range of connection options. Proven in small to medium-sized filter systems.

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 2 m above or max. 3 m below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 0.5 l Suction screen mesh size approx. 2.8 x 2.8 mm

Material short text

BADU Magic II/11, 1~, 0,45kW,m.Kabel+St.

Technical data

Hydraulic power

Flow rate	11 m³/h
Förderhöhe	0 – 12.7 mWS

Motor & drive

Drehzahl	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.72 kW

Power output P_2 (max.)	0.45 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	0.5 l

Connections & piping

Connection, inlet / suction side	50 mm/ 1 1/2 Rp
Connection, discharge side	50 mm/ 1 1/2 Rp
Recommended suction line diameter	50 mm
Recommended discharge line diameter	50 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	488 mm
Product width	130 mm
Product height	319 mm
Net weight	7.3 kg
Customs tariff number	84137051