BADU PICCO II

BADU Picco II

Article number	2191028038
GTIN/EAN	4260673450533
Product page	https://www.speck-pumps.com/en/p/badu-picco-ii-2191028038



Description

Compact, versatile, and designed for flexible hose connections. Designed for small and above-ground pools.

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 1.5 m above or max. 3 m below the water level.

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the water in the circuit. Electrically isolated. Fiber catcher capacity approx. 0.5 l Suction screen mesh size approx. 2.8 x 2.8 mm

Material short text

BADU Picco II, 1~, 0,20kW, mit 3,5m

Technical data

Hydraulic power

Flow rate	6 m³/h
Förderhöhe	11 mWS

Motor & drive

Drehzahl	2,840 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0.39 kW

Power output P_2 (max.)	0.2 kW
Voltage (max.)	1~ 230 V
Frequency	50 Hz
Cable length	3.5 m

General / Product features

Product range	BADU Allround
Certification	TÜV

Filtration

Lint catcher capacity	0.5 l
Strainer basket version	1

Connections & piping

Connection, inlet / suction side	32 mm
Connection, discharge side	32 mm/38 mm
Recommended suction line diameter	40 mm

Operating conditions & water

Total salt concentration	5 g/l

Dimensions & logistics

Product length	418 mm
Product width	170 mm
Product height	324 mm
Net weight	5.6 kg
Customs tariff number	84137051