
BADU RESORT

BADU Resort 55

Article number	2195558037
GTIN/EAN	4260673451820
Product page	https://www.speck-pumps.com/en/p/badu-resort-55-2195558037



Description

Cost-saving large-scale system pump Low weight and high power For wellness oases, hotel swimming pools or special pools

Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 10 l Suction screen mesh size approx. 3.4 x 3.2 mm

Material short text

BADU Resort 55, 3~, 4,00kW, blau

Technical data

Hydraulic power

Flow rate	55 m³/h
Förderhöhe	0 – 24.5 mWS
Operating pressure max.	0 bar

Motor & drive

Drehzahl	2,840 min-1
Motor phases	3~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	4.54 kW
Power output P_2 (max.)	4 kW
Voltage (max.)	3~ Y/Δ 690/400 V
Frequency	50 Hz

Filtration

Lint catcher capacity	10 l

Connections & piping

Connection, inlet / suction side	110 mm
Connection, discharge side	110 mm
Recommended suction line diameter	110 mm
Recommended discharge line diameter	110 mm

Operating conditions & water

Umgebungstemperatur	40 ° C
Total salt concentration	5 g/l

Dimensions & logistics

Product length	860 mm
Product width	0 mm
Product height	0 mm
Net weight	43.4 kg
Customs tariff number	84137051