IN-VC(-S) 15

IN-VC 15-80 F

Article number 6271508067

Product page https://www.speck-pumps.com/en/p/in-vc-15-80-f-6271508067



Description

The vertical, multi-stage centrifugal pumps are non-self-priming high-pressure centrifugal pumps characterized by high efficiency and a long service life. All parts in contact with the medium are made of stainless steel.

Areas of use

Pressure booster systems Water treatment Sprinkling and irrigation Fire extinguishing systems Cooling water supply

Material short text

IN-VC 15-80-F23F-3A5-110

Technical data

Hydraulic power

Flow rate	22.5 m³/h
Förderhöhe	125 mWS
Operating pressure max.	16 bar

Motor & drive

Drehzahl	2,850 min-1
Motor phases	3~
Motor frame size	160
Degree of protection	IP 55
Insulation class	F

Electrics

Power output P_2 (max.)	11 kW
Voltage (max.)	3~ 690/400 V ± 10 %
Frequency	50 Hz

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, inlet / suction side	DN 50
Connection, discharge side	DN 50

Operating conditions & water

Umgebungstemperatur	40 ° C

Dimensions & logistics

Net weight	189 kg
Customs tariff number	84137089