IN-VC(-S) 15

# IN-VC 15-100 F

Article number 6271510067

Product page https://www.speck-pumps.com/en/p/in-vc-15-100-f-6271510067



## Description

The vertical, multi-stage centrifugal pumps are non-self-priming high-pressure centrifugal pumps characterized by high efficiency and a long service life. All parts in contact with the medium are made of stainless steel.

## Areas of use

Pressure booster systems Water treatment Sprinkling and irrigation Fire extinguishing systems Cooling water supply

## Material short text

IN-VC 15-100-F23F-3A5-110

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 22.5 m³/h |
| Förderhöhe | 156 mWS |
| Operating pressure max. | 16 bar |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 min-1 |
| Motor phases | 3~ |
| Motor frame size | 160 |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power output $P_2$ (max.) | 11 kW |
| Voltage (max.) | 3~ 690/400 V ± 10 % |
| Frequency | 50 Hz |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | IE3 |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | DN 50 |
| Connection, discharge side | DN 50 |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur | 40 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 197 kg |
| Customs tariff number | 84137089 |