NORMBLOCK MULTI 65/250

# Normblock Multi 65-250

Product page https://www.speck-pumps.com/en/p/normblock-multi-65-250-p53060



## Description

Characteristic curves, as well as dimensional drawings and the various material combinations can be found in detail in our design program at speck-select.com

## Areas of use

Swimming pool water circulation for filtration and filter flushing, as well as the operation of swimming pool attractions in public swimming pools. > Outdoor and indoor pools > Thermal, medicinal, and spa baths > Pools with elevated brine concentrations > Water treatment, e.g., filter system construction > Leisure facilities > Attractions, e.g., water slides > Shipbuilding > Industry, e.g., cooling water systems > Water supply, e.g., irrigation

## Version

The Normblock Multi is a single-stage, non-self-priming volute casing pump with power allocation and main dimensions according to NF E 44-112 and DIN EN 733 (replacement for DIN 24255).

## Material short text

NBM 65/250

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 0 – 100 m³/h |
| Förderhöhe | 0 – 25.5 mWS |
| Operating pressure max. | 3 bar |

### Motor & drive

| | |
|---|---|
| Motor phases | 3~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | IE3 |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | DN 80 |
| Connection, discharge side | DN 65 |
| Recommended suction line diameter | 0 mm |
| Recommended discharge line diameter | 0 mm |

### Operating conditions & water

| | |
|---|---|
| Total salt concentration | 0 g/l |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 7.5 kW |
| Power output $P_2$ (max.) | 6 kW |
| Voltage (max.) | 400 V |
| Frequency | 50 Hz |

## Dimensions & logistics

| | |
|---|---|
| Product length | 738.5 mm |
| Product width | 0 mm |
| Product height | 208 mm |