NP10

NP10-13-150

Product page https://www.speck-pumps.com/en/p/np10-13-150-p53072



Description

High-pressure plunger pumps of the NP 10 series are oscillating positive displacement pumps and therefore offer high efficiency because the fluid is moved directly and with minimal loss. Compared to rotating positive displacement pumps, they enable more precise pumping at high pressures and low flow rates, making them particularly efficient for demanding applications.

Sales text

NP10/13-150

Areas of use

>High-pressure cleaning: They ensure effective high-pressure cleaning. >Air humidification: They ensure even and efficient air humidification. >Fire extinguishing systems: They are used in fire extinguishing systems for safe firefighting. >Sewer cleaning: They support the efficient cleaning of sewers.

Technical data

Hydraulic power

Flow rate	13.1 l/min
Förderhöhe	1,529.574 mWS
Operating pressure max.	150 bar

Motor & drive

Drehzahl	1,450 min-1

Electrics

Power input max.	4 kW
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2x G3/8" / 2x 1/2"

Connection, discharge side	2x G3/8"

Operating conditions & water

Umgebungstemperatur	40 ° C
Temperature min.	70 ° C

Dimensions & logistics

Customs tariff number	84135080