
NP30

NP30-140-100

Product page https://www.speck-pumps.com/en/p/np30-140-100-p53100



Description

High-pressure plunger pumps of the NP 30 series are oscillating positive displacement pumps and therefore offer high efficiency because the pumped medium is moved directly and with minimal loss. Compared to rotating positive displacement pumps, they enable more precise pumping at high pressures and low flow rates, making them particularly efficient for demanding applications.

Sales text

NP30/140-100

Areas of use

>High-pressure cleaning: They ensure effective high-pressure cleaning. >Air humidification: They ensure even and efficient air humidification. >Fire extinguishing systems: They are used in fire extinguishing systems for safe firefighting. >Sewer cleaning: They support the efficient cleaning of sewers.

Technical data

Hydraulic power

Flow rate	134 l/min
Förderhöhe	1,019.716 mWS
Operating pressure max.	100 bar

Motor & drive

Drehzahl	1,450 min-1

Electrics

Power input max.	26.3 kW
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2x G 1 1/2"

Connection, discharge side	2x G1"

Operating conditions & water

Umgebungstemperatur	40 ° C
Temperature min.	70 ° C

Dimensions & logistics

Customs tariff number	84135080