
P52

P52-30-500 MS

Product page https://www.speck-pumps.com/en/p/p52-30-500-ms-p53148



Description

High-pressure plunger pumps of the P 52 series are oscillating positive displacement pumps and therefore offer high efficiency because the pumped medium is moved directly and with minimal loss. Compared to rotating positive displacement pumps, they enable more precise pumping at high pressures and low flow rates, making them particularly efficient for demanding applications.

Sales text

P52/30-500 MS

Areas of use

>High-pressure cleaning: They ensure effective high-pressure cleaning. >Air humidification: They ensure even and efficient air humidification. >Fire extinguishing systems: They are used in fire extinguishing systems for safe firefighting. >Sewer cleaning: They support the efficient cleaning of sewers.

Technical data

Hydraulic power

Flow rate	30 l/min
Förderhöhe	5,098.58 mWS
Operating pressure max.	500 bar

Motor & drive

Drehzahl	1,000 min^{-1}

Electrics

Power input max.	30.2 kW
Frequency	50 Hz

Connections & piping

Connection, inlet / suction side	2x G3/4"

Connection, discharge side	2x G1/2"

Operating conditions & water

Umgebungstemperatur max.	40 ° C
Medientemperatur max.	70 ° C

Dimensions & logistics

Customs tariff number	84135080