SFE 2-40

# SFE 2/40-40-2

Article number 5624004250

Product page https://www.speck-pumps.com/en/p/sfe-2-40-40-2-5624004250



## Description

The fully automatic multi-pump pressure boosting systems are equipped with two to six pumps, depending on requirements. They are compact, quiet, and delivered fully wired and piped. All units feature a fully automatic pump control system. The pressure boosting system is equipped with a frequency controller.

## Areas of use

Drinking water supply Industrial water supply Process water supply Air conditioning systems Irrigation and watering

## Version

With 2-6 non-self-priming multistage centrifugal pumps and speed control for each pump (frequency converter), in accordance with DIN 1988-500. Pumped medium: Drinking water. Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages Special elastomers Special mechanical seals Higher fluid temperatures Larger systems

## Material short text

Multicell SFE 2/40-40-2 Dr., Zulaufbetr.

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 40 m³/h |
| Förderhöhe | 72.4 – 91.774 mWS |
| Flow rate of standby pump | 40 m³/h |
| Operating pressure max. | 10 bar |
| Number of pumps | 2 St |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 $min^{-1}$ |
| Degree of protection | IP 55 |

| | |
|---|---|
| Insulation class | F |

**Electrics**

| | |
|---|---|
| Leistungsabgabe $P_2$ max. | 15 kW |
| Input voltage | 400 V |
| Frequency | 50 Hz |

**Energy efficiency**

| | |
|---|---|
| Energy efficiency class | IE3 |

**Connections & piping**

| | |
|---|---|
| Connection, inlet / suction side | 100 DN |
| Connection, discharge side | 100 DN |

**Operating conditions & water**

| | |
|---|---|
| Umgebungstemperatur max. | 40 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 635 kg |
| Gross weight | 685 kg |
| Customs tariff number | 84798997 |