SPR-H FÜR 2 PUMPENANLAGEN

# SPR-H 020-475-P

Article number 5606427501

Product page https://www.speck-pumps.com/en/p/spr-h-020-475-p-5606427501



## Description

The frequency control for single- and multi-pump pressure boosting systems is supplied as a steel-enclosed control cabinet and ensures optimal adaptation of the pump to the application.

## Areas of use

Water supply Cooling circuit Irrigation Industrial applications

## Version

The SPR-H speed controller optimally adapts the pump to the system. The pump controller is available for the following control types: Constant pressure control Temperature control Level control Vacuum control. The SPR-H speed controller is supplied as an IP 54 steel-enclosed control cabinet. The speed controller is equipped with a plain-text display, keypad, main switch, and motor protection. The system is factory-configured. Fuses are provided for each pump, a H-0-A switch for each pump, and a PTC thermistor connection. Special versions Remote control Remote monitoring via GSM module Water meter Pre-feed monitoring/refilling

## Material short text

SPR-H 020-475-P, 37 kW

## Technical data

### Motor & drive

| | |
|---|---|
| Motor phases | 3~ |
| Degree of protection | IP 54 |

### Electrics

| | |
|---|---|
| Power output $P_2$ (max.) | 37 kW |
| Voltage (max.) | 3~ 400 V |
| Frequency | 50 Hz |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur | 0 ° C |
| Temperature min. | 0 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 280 kg |
| Customs tariff number | 85371098 |