TOP 73

TOP 73 D

Article number 6420300007

Product page https://www.speck-pumps.com/en/p/top-73-d-6420300007



Description

Optimal drainage through submersible pumps made of corrosion-resistant materials from Speck, offering a highly flexible application and use for more than just water.

Areas of use

Basement drainage Drainage of pump shafts Wastewater disposal Rainwater pumping Groundwater pumping

Version

Fully submersible submersible pump made of stainless steel. Motor with built-in thermal overload protection (for AC). Ready to connect with a 10 m cable and Schuko plug (for AC), with a free cable end (for three-phase). AC = AC 1~ 230 V, with floating switch D = Three-phase 3~ 400 V, without floating switch VOX = Open impeller Pump medium: Pure water, wastewater, and dirty water, without long-fiber components.

Material short text

TOP 73 D, 0,75 kW

Technical data

Hydraulic power

Flow rate	17 m³/h
Förderhöhe	14.5 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	3~
Degree of protection	IP 68
Insulation class	F

Electrics

Power input P_1 (max.)	1.2 kW
Power output P_2 (max.)	0.75 kW
Voltage (max.)	3~ 400 V
Frequency	50 Hz
Cable length	10 m

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, discharge side	1 1/2 Rp

Dimensions & logistics

Product length	0 mm
Product width	210 mm
Product height	352 mm
Net weight	12.9 kg
Gross weight	13 kg
Customs tariff number	84137021