TOP 74

TOP 74 D

Article number 6420400007

Product page https://www.speck-pumps.com/en/p/top-74-d-6420400007



Description

Optimal drainage through submersible pumps made of corrosion-resistant materials from Speck, offering a highly flexible application and use for more than just water.

Areas of use

Basement drainage Drainage of pump shafts Wastewater disposal Rainwater pumping Groundwater pumping

Version

Fully submersible submersible pump made of stainless steel. Motor with built-in thermal overload protection (for AC). Ready to connect with a 10 m cable and Schuko plug (for AC), with a free cable end (for three-phase). AC = AC 1~ 230 V, with floating switch D = Three-phase 3~ 400 V, without floating switch VOX = Open impeller Pump medium: Pure water, wastewater, and dirty water, without long-fiber components.

Material short text

TOP 74 D, 1,10 kW

Technical data

Hydraulic power

Flow rate	20 m³/h
Förderhöhe	18 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	3~
Degree of protection	IP 68
Insulation class	F

Electrics

Power input P_1 (max.)	1.6 kW
Power output P_2 (max.)	1.1 kW
Voltage (max.)	3~ 400 V
Frequency	50 Hz
Cable length	10 m

Energy efficiency

Energy efficiency class	IE3

Connections & piping

Connection, discharge side	1 1/2 Rp

Dimensions & logistics

Product length	0 mm
Product width	210 mm
Product height	377 mm
Net weight	14 kg
Gross weight	15.4 kg
Customs tariff number	84137021