2 VGX 7

2 VGX 7/10

Article number 6412102138A

Product page https://www.speck-pumps.com/en/p/2-vgx-7-10-6412102138a



Description

Horizontal, single- or two-stage pumps in close-coupled design. They are characterized by a compact design and a long service life. All wetted parts are made of stainless steel.

Areas of use

Water treatment Water supply Cooling systems Apparatus construction

Version

Close-coupled pump with surface-cooled motor, extended motor shaft for the impellers, shaft sealing by a mechanical seal, designed for continuous operation. Fluid: Clear, even moderately aggressive liquids that do not chemically or mechanically attack the pump materials. Special designs: Special voltages: Special elastomers: Special mechanical seals: Higher fluid temperatures:

Material short text

VGX 20/20, 1~, 1,50 kW

Technical data

Hydraulic power

Flow rate	4.8 m³/h
Förderhöhe	41 mWS

Motor & drive

Drehzahl	2,850 min-1
Motor phases	1~
Degree of protection	IP 55
Insulation class	F

Electrics

Power input P_1 (max.)	0 kW
Power output P_2 (max.)	0.9 kW
Voltage (max.)	1~ 230 V ± 10 %
Frequency	50 Hz

Dimensions & logistics

Net weight	14 kg
Customs tariff number	84137075