BADU DELTA DR.

# BADU Delta 22

| | |
|---|---|
| Article number | 2103220037 |
| GTIN/EAN | 4260673450885 |
| Product page | https://www.speck-pumps.com/en/p/badu-delta-22-2103220037 |



## Description

New high-class standard for demanding projects High-quality filter circulation pumps for professionals

## Areas of use

Swimming pool water circulation in filter systems, can be installed max. 3 m above or below the water level

## Version

Close-coupled pump with integrated fiber catcher. Bellows mechanical seal mounted on a plastic impeller hub. The motor or pump shaft does not come into contact with the circulating water. Electrically isolated. Fiber catcher capacity approx. 4 l Suction screen mesh size approx. 2.2 x 2.2 mm

## Material short text

BADU Delta 22, 3~, 0,75 kW

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate | 22 m³/h |
| Förderhöhe | 15 mWS |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,840 min-1 |
| Motor phases | 3~ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Power input $P_1$ (max.) | 0.9 kW |

| | |
|---|---|
| Power output $P_2$ (max.) | 0.75 kW |
| Voltage (max.) | 3~ Y/Δ 400/230 V |
| Frequency | 50 Hz |

**General / Product features**

| | |
|---|---|
| Certification | TÜV, Garantie 5 Jahre, Patent |

**Filtration**

| | |
|---|---|
| Lint catcher capacity | 4 l |

**Connections & piping**

| | |
|---|---|
| Connection, inlet / suction side | 63 mm |
| Connection, discharge side | 63 mm |
| Recommended suction line diameter | 63 mm |
| Recommended discharge line diameter | 63 mm |

**Operating conditions & water**

| | |
|---|---|
| Umgebungstemperatur | 40 ° C |
| Total salt concentration | 5 g/l |

## Dimensions & logistics

| | |
|---|---|
| Product length | 572 mm |
| Net weight | 15.4 kg |
| Customs tariff number | 84137051 |