MULTICELL SFE 4

# SFE 4/25-70

Article number 5642507500

Product page https://www.speck-pumps.com/en/p/sfe-4-25-70-5642507500



## Description

Die vollautomatischen Mehrpumpdruckerhöhungs-Anlagen sind je nach Bedarfsfall mit 2 bis 6 Pumpen ausgestattet. Sie sind kompakt, geräuscharm und werden anschlussfertig verdrahtet und komplett verrohrt ausgeliefert. Alle Aggregate besitzen eine vollautomatische Pumpensteuerung. Die Druckerhöhungs-Anlage ist mit einer Frequenzregelung ausgestattet.

Die angegebenen Leistungswerte beziehen sich auf unsere Standardausführungen. Individuelle, projektbezogene Anpassungen sind auf Anfrage möglich.

## Material short text

Multicell SFE 4/25-70 Dr., Zulaufbetrieb

## Technical data

### Hydraulic power

| | |
|---|---|
| Flow rate of standby pump | 25 m³/h |
| Target pressure | 11.7 bar |

### Motor & drive

| | |
|---|---|
| Drehzahl | 2,850 $min^{-1}$ |
| Degree of protection | IP 55 |
| Insulation class | F |

### Electrics

| | |
|---|---|
| Leistungsabgabe $P_2$ max. | 15 kW |
| Input voltage | 400 V |
| Rated current (400V) | 26.2 A |
| Frequency | 50 Hz |

### Energy efficiency

| | |
|---|---|
| Energy efficiency class | IE3 |

### Connections & piping

| | |
|---|---|
| Connection, inlet / suction side | 125 DN |
| Connection, discharge side | 125 DN |

### Operating conditions & water

| | |
|---|---|
| Umgebungstemperatur max. | 40 ° C |

## Dimensions & logistics

| | |
|---|---|
| Net weight | 1,200 kg |